	1 2	3	4	5	6 7	
	PUBLICATIO	DN If this document is it is for information	printed in hardcopy, use only and therefore ating controls. Always latest issue.	is E	THIS DRAWING IS CONFIDE IT SHALL NOT BE LOANED (FOR ANY OTHER PURPOSE	
	P12.320	refer to viewer for	latest issue.	FIRST ANGLE PROJECTION	FOR ANT OTHER PURPOSE	
н	ISSUE : 1			NISSAN STANDARD HUB MTGS		
	Skyline R32/3 Front Kit Number CP5555-1000			INCLUDED FOR REF		
	Ref Description	Qtv ARF	ROW TO SHOW			
	1 Caliper RH Caliper LH	DIRECT	ION OF ROTATION		(7) (10)	
	2 Disc RH					
G	2 Disc LH 3 Mtg Bell					
	4 Disc Bolt 5 Disc Bolt Washer	24 48				
	6 Disc Bolt Nut	24				
	7 Mtg Bracket Bracket Bolt	2		· · · · · · · · · · · · · · · · · · ·		
	8 <u>M12x1.75x62.5</u> 9 M12 Washer	4				
F	10 0.5mm Washer/Shim	12				
	11 Cleveloc Nut Pipe Assy RH		0			
	12 Pipe Assy LH 13 Banjo Fitting	2 2				
	14 Gasket	4				
	15 Banjo-M10 16 Washer	2 4				
	17 Caliper Mtg Bolt M12x1.75x73.85		0			
Е	18 Anti-Rattle Clip					
	19 Pad Retainer Insert20 Pad Retainer Bolt					
	21 Pad Set (4)		0			
			$\checkmark 0 $			
	(\frown			(20)	
D	(4)6/01	
					20-1-0	
		5 2			Conserved and the served of th	
		3		-1 00 fl		
				O A FT A		
			(20)			
С						
	Part Ref #	ning Torques Torque	() ()			
	Bolt/Nut Ref 8/11	68NM		- Col		
	Bolt Ref 17	68NM 25NM	0)			
	Banjo Bolt Ref 15 Bolt/Nut Ref 4/6	14NM				
в	Caliper Bleed Screw	17NM		(21)		
	Pad Retaining Pin Ref 20	19NM				
	BRAKE DIS					
	NEW	MINWORN				
	32.00mm	31.00mm				
	Check caliner is central over	disc, Use 0.5mm shims (Part ref 10)	to adjust if		A PICTORIAL VIEW FO	
Α	-	san bracket and grommet to locate hy	-	SUPPLI	SOME PARTS MAY VAR ED. AP RACING RESER	
	Hydraulic pipe should	d be bent and located as shown in ph	oto.	TO CHA NOTICE	NGE COMPONENTS W	

